



KERAV INITIAL APP CAT A/B/C/D VOR RWY34

Navigation Performance	Path Terminator	WPT Name	Latitude (N) / Longitude (W)	Fly-By or Fly-Over	Distance (NM)	True Track / Magnetic Track	Upper Limit/Lower Limit	Speed Limit (kts)	Remarks
RNAV1	IF	KERAV	533742.7 / 0054557.3	Fly-By	-	-	-	-	-
RNAV1	TF	AMDIL	531525.3 / 0055853.4	Fly-By	23.6	199.2 / 203	-	-	-
RNAV1	TF	INTOP	531327.4 / 0060632.4	Fly-By	5.0	246.9 / 250	+ 3000	180	-

SORIN INITIAL APP CAT A/B/C/D VOR RWY34

Navigation Performance	Path Terminator	WPT Name	Latitude (N) / Longitude (W)	Fly-By or Fly-Over	Distance (NM)	True Track / Magnetic Track	Upper Limit/Lower Limit	Speed Limit (kts)	Remarks
RNAV1	IF	SORIN	530829.3 / 0054822.5	Fly-By	-	-	-	-	-
RNAV1	TF	INTOP	531327.4 / 0060632.4	Fly-By	12.0	294.6 / 298	+ 3000	180	-

RWY 34 VOR Approach

Descent Angle:	3.00'						
Fix	IF (INTOP)	FAF (ABDOX)	SDF	MAPt	BAPDA (MATF)	DAP	SORIN
Fix Coordinates	531327.4N 0060632.4W	531716.9N 0060916.8W	532047.7N 0061148.3W	532416.8N 0061418.9W	533740.0N 0062403.7W	532525.2N 0061810.3W	530829.3N 0054822.5W
Fix Formation Bearing °T	156.62 DUB	156.62 DUB	156.62 DUB	156.62 DUB	336.51 DUB	-	133.28 DAP
Fix Formation Distances	18.0 DUB	13.83 DUB	10.00 DUB	6.20 DUB	8.42 DUB	-	24.65 DAP

Holding Identification - KERAV

Holding Fix	Latitude (N) / Longitude (W)	Inbound True Track (degrees)	Inbound Magnetic Track (degrees)	Direction of Turn	Maximum Indicated Airspeed (kts)	Maximum/ Minimum Holding Level / Altitude (FL/ft)	Distance outbound (NM)
KERAV	533742.7 / 0054557.3	205.5	209	R	230	FL140 / 5000	5.4

Holding Identification - SORIN

Holding Fix	Latitude (N) / Longitude (W)	Inbound True Track (degrees)	Inbound Magnetic Track (degrees)	Direction of Turn	Maximum Indicated Airspeed (kts)	Maximum/ Minimum Holding Level / Altitude (FL/ft)	Distance outbound (NM)
SORIN	530829.3 / 0054822.5	342.3	346	L	230	FL140 / 5000	5.4

Note: Hold is contingency only & will only be used when directed by ATC.