



Navigation Performance	Path Terminator	WPT Name	Latitude (N) / Longitude (W)	Fly-By or Fly-Over	Distance (NM)	True Track / Magnetic Track	Upper Limit / Lower Limit	Speed Limit (kts)	VPA / TCH	Remarks
RNP APCH	IF	KY019	521955.6 / 0091120.4	Fly-By	-	-	+3900	-	-	IAF
RNP APCH	TF	INRAD	521528.8 / 0090901.3	Fly-By	4.7	162.1 / 166	+3000	-	-	IF
RNP APCH	TF	ROTSO	521329.3 / 0091850.6	Fly-By	6.4	252.1 / 256	@3000	-	-	FAF
RNP APCH	TF	KY012	521237.7 / 0092253.3	Fly-By	2.6	250.9 / 255	+2020	-	-	SDF
RNP APCH	TF	KY013	521159.3 / 0092558.2	Fly-By	2.0	251.4 / 255	+1280	-	-	SDF
RNP APCH	TF	RW26	521101.6 / 0093035.8	Fly-Over	3.0	251.3 / 255	-	-	3.50 / 49	-
RNP APCH	CF	KY018	520948.2 / 0093655.9	Fly-Over	4.0	252.6 / 257	- 3000	180	-	L
RNP APCH	CF	KER NDB	521055.8 / 0093128.2	-	3.6	012.5 / 016	@3000	180	-	-

Navigation Performance	Path Terminator	WPT Name	Latitude (N) / Longitude (W)	Fly-By or Fly-Over	Distance (NM)	True Track / Magnetic Track	Upper Limit / Lower Limit	Speed Limit (kts)	VPA / TCH	Remarks
RNP APCH	IF	KY015	521640.6 / 0090247.1	Fly-By	-	-	+3700	-	-	IAF
RNP APCH	TF	INRAD	521528.8 / 0090901.3	Fly-By	4.0	252.1 / 256	+3000	-	-	IF
RNP APCH	TF	ROTSO	521329.3 / 0091850.6	Fly-By	6.4	252.1 / 256	@3000	-	-	FAF
RNP APCH	TF	KY012	521237.7 / 0092253.3	Fly-By	2.6	250.9 / 255	+2020	-	-	SDF
RNP APCH	TF	KY013	521159.3 / 0092558.2	Fly-By	2.0	251.4 / 255	+1280	-	-	SDF
RNP APCH	TF	RW26	521101.6 / 0093035.8	Fly-Over	3.0	251.3 / 255	-	-	3.50 / 49	-
RNP APCH	CF	KY018	520948.2 / 0093655.9	Fly-Over	4.0	252.6 / 257	- 3000	180	-	L
RNP APCH	CF	KER NDB	521055.8 / 0093128.2	-	3.6	012.5 / 016	@3000	180	-	-

Navigation Performance	Path Terminator	WPT Name	Latitude (N) / Longitude (W)	Fly-By or Fly-Over	Distance (NM)	True Track / Magnetic Track	Upper Limit / Lower Limit	Speed Limit (kts)	VPA / TCH	Remarks
RNP APCH	IF	KY020	521120.9 / 0090649.9	Fly-By	-	-	+4500	-	-	IAF
RNP APCH	TF	INRAD	521528.8 / 0090901.3	Fly-By	4.3	342.2 / 346	+3000	-	-	IF
RNP APCH	TF	ROTSO	521329.3 / 0091850.6	Fly-By	6.4	252.1 / 256	@3000	-	-	FAF
RNP APCH	TF	KY012	521237.7 / 0092253.3	Fly-By	2.6	250.9 / 255	+2020	-	-	SDF
RNP APCH	TF	KY013	521159.3 / 0092558.2	Fly-By	2.0	251.4 / 255	+1280	-	-	SDF
RNP APCH	TF	RW26	521101.6 / 0093035.8	Fly-Over	3.0	251.3 / 255	-	-	3.50 / 49	-
RNP APCH	CF	KY018	520948.2 / 0093655.9	Fly-Over	4.0	252.6 / 257	- 3000	180	-	L
RNP APCH	CF	KER NDB	521055.8 / 0093128.2	-	3.6	012.5 / 016	@3000	180	-	-

Holding Procedure: KER NDB

Holding Fix	Latitude (N) / Longitude (W)	Inbound True Track (degrees)	Inbound Magnetic Track (degrees)	Direction of Turn	Maximum Indicated Airspeed (kts)	Maximum / Minimum Holding Level / Altitude (FL/ft)	Distance outbound (NM)
KER NDB	521055.8 / 0093128.2	250.5	255	R	220	FL100 / 3000	3.7

Runway 26 LNAV/VNAV – Procedure unavailable if OAT is less than -10°C unless avionics include approved temperature compensation.

Runway 26 LNAV/VNAV – Note VPA may exceed 3.5° if OAT is higher than 14°C.